



# IKO BEARING MANUFACTURING LIMITED

## NTN ucfl205d1 Bearing



Bearing No. ucfl205d1

ucfl205d1 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.59
EAN	4547359001013
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	14 Millimeter
Relubricatable	Yes
Insert Part Number	UC205D1
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Metric
Long Description	2 Bolt Flange Block; 25MM Bore; 99MM Bolt Circle; 99MM Bolt Spacing; 1 Piece Solid; Set Screw Mount; Cast Iron; Ball Bearing; 34MM Length Thru Bore; Relubricatable; Single Lip Land Riding Seals



# IKO BEARING MANUFACTURING LIMITED

Other Features	Single Row   Light Duty   Wide Inner Race   Has Flinger
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	UCFL205D1
Weight / LBS	1.3
d	0.984 Inch   25 Millimeter
Nominal Bolt Circle Diameter Round	3.9 Inch   99 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Bolt Spacing	3.9 Inch   99 Millimeter
D	1.339 Inch   34 Millimeter
bore diameter:	25 mm
radial dynamic load capacity:	3150 lb
bolt center-to-center length:	3.8906 in
radial static load capacity:	1770 lb
overall length/diameter:	5.1250 in
seal type:	Contact with Flinger
bore type:	Round
length through bore:	1-13/32 in
duty type:	Light Duty
finish/coating:	Uncoated
mounting type:	Two-Bolt Flange
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	UCFL2



## IKO BEARING MANUFACTURING LIMITED

locking device:	Set Screw
standards met:	ISO, AFBMA
expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing:	UC205D1